according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikaflex®-265 DG-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Sealant/adhesive.

# 1.3 Details of the supplier of the safety data sheet

Company : Sika Netherlands BV

Zonnebaan 56 3542 EG Utrecht

Telephone : +31302410120 E-mail address : EHS@nl.sika.com

# 1.4 Emergency telephone number

Emergency telephone num: +31570854201

ber

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Type of product : Mixture

### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

# Classification (67/548/EEC, 1999/45/EC)

Sensitising R42: May cause sensitisation by inhalation.

Irritant R36/38: Irritating to eyes and skin.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

Hazard pictograms

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

P285 In case of inadequate ventilation wear res-

piratory protection.

Response:

P304 + P341 IF INHALED: If breathing is difficult, remove

victim to fresh air and keep at rest in a posi-

tion comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label:

• 202-966-0 4,4'-methylenediphenyl diisocyanate

# **Additional Labelling:**

EUH204 Contains isocyanates. May produce an allergic reaction.

#### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

## **Hazardous components**

Chemical Name	Classification	Classification	Concentration
CAS-No.	(67/548/EEC)	(REGULATION	[%]
EC-No.		(EC) No	
Registration number		1272/2008)	
Hydrocarbons, C9-C12, n-alkanes,	Xn; R65	Asp. Tox.1; H304	>= 1 - < 2,5
isoalkanes, cyclics, aromatics (2-25%)	R10	Flam. Liq.3; H226	
64742-82-1	R66	STOT SE3; H336	
919-446-0	R67	Aquatic Chronic2;	

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

265-185-4 01-2119458049-33-XXXX	N; R51/53	H411	
4,4'-methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47-XXXX	Carc.Cat.3; R40 Xn; R20-R48/20 Xi; R36/37/38 R42/43	Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT RE2; H373	>= 0,1 - < 1
dibutyltin dichloride 683-18-1 211-670-0 01-2119496066-31-XXXX	Repr.Cat.2; R60- R61 Mut.Cat.3; R68 T+; R26 T; R25-R48/25 C; R34 Xn; R21 N; R50/53	Muta.2; H341 Repr.1B; H360FD Acute Tox.2; H330 Acute Tox.3; H301 Acute Tox.4; H312 STOT RE1; H372 Skin Corr.1B; H314 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,01 - < 0,025

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

# 4.2 Most important symptoms and effects, both acute and delayed

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Version 1.0 Revision Date 03.03.2015 Print Date 03.03.2015

**Symptoms** : Asthmatic appearance

> Allergic reactions **Excessive lachrymation**

Erythema **Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

# 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

# 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015

Version 1.0 Print Date 03.03.2015

acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe

: Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

# 8.2 Exposure controls

#### Personal protective equipment

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Revision Date 03.03.2015 Version 1.0

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

# **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : paste Colour : black

Odour : odourless

Odour Threshold : No data available

Flash point : > 200 °C

Ignition temperature : Not applicable

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : No data available

Melting point/range / Freez-

ing point

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,23 g/cm3

at 20 °C

: No data available

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015 Version 1.0



# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute toxicity**

## **Components:**

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Test atmosphere: dust/mist Method: Expert judgement

dibutyltin dichloride:

Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Converted acute toxicity point estimate

Skin corrosion/irritation

**Product:** 

Remarks: Causes skin irritation.

Serious eye damage/eye irritation

**Product:** 

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

**Product:** 

Remarks: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

**Product:** 

Germ cell mutagenicity- As-

: No data available

sessment

Carcinogenicity

**Product:** 

Carcinogenicity - Assess-

: No data available

ment

Reproductive toxicity

**Product:** 

Reproductive toxicity - As- : No data available

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

sessment

No data available

# **SECTION 12: Ecological information**

# 12.1 Toxicity

# Components:

# dibutyltin dichloride:

Toxicity to daphnia and other : EC50: 1,4 mg/l, 48 h, Daphnia (water flea)

aquatic invertebrates

M-Factor

: 10

# 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

# **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3



Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

: 08 04 09\* waste adhesives and sealants containing organic European Waste Catalogue

solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

# **SECTION 14: Transport information**

#### **ADR**

Not dangerous goods

IATA

Not dangerous goods

**IMDG** 

Not dangerous goods

# 14.6 Special precautions for user

No data available

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

Hazard pictograms



Harmful

: R36/38 R-phrase(s) Irritating to eyes and skin.

> R42 May cause sensitisation by inhalation.

S-phrase(s) : S23 Do not breathe vapour.

> S45 In case of accident or if you feel unwell,

seek medical advice immediately (show

the label where possible).

Hazardous components which must be listed on the label:

202-966-0 4,4'-methylenediphenyl diisocyanate

Special labelling of certain

: Contains isocyanates. See information supplied by the manumixtures

facturer.

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015 Version 1.0 Print Date 03.03.2015

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

preparations and articles (Annex XVII)

: Banned and/or restricted

(1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-

rich)

(4,4'-methylenediphenyl diisocya-

nate)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

VOC-CH (VOCV) : 2 %

no VOC duties

VOC-EU (solvent) : 2 %

# 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

# **SECTION 16: Other information**

#### **Full text of R-Phrases**

KIU	riammable.
R20	Harmful by inhalation.
R21	Harmful in contact with skin.
R25	Toxic if swallowed.
R26	Very toxic by inhalation.
R34	Causes burns.

Elommobio

R36/37/38 Irritating to eyes, respiratory system and skin.
Limited evidence of a carcinogenic effect.

R42/43 May cause sensitisation by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure

through inhalation.

R48/25 Toxic: danger of serious damage to health by prolonged exposure if

swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R60 May impair fertility.

R61 May cause harm to the unborn child.

according to Regulation (EC) No. 1907/2006

# Sikaflex®-265 DG-3

Revision Date 03.03.2015



R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Version 1.0

R67 Vapours may cause drowsiness and dizziness.

R68 Possible risk of irreversible effects.

#### **Full text of H-Statements**

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if in-

haled.

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Acute Acute aquatic toxicity Aquatic Chronic Chronic aquatic toxicity Asp. Tox. Aspiration hazard Carc. Carcinogenicity Eve Irrit. Eye irritation Flam. Liq. Flammable liquids Muta. Germ cell mutagenicity Reproductive toxicity Repr. Resp. Sens. Respiratory sensitisation

Skin Corr. Skin corrosion
Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikaflex®-265 DG-3

Revision Date 03.03.2015 Version 1.0

